



THE UNIVERSITY OF
**WESTERN
AUSTRALIA**

Exit status and conditionals

Lecture 6

Michael J. Wise

Meaning of *True*

- When programs conclude, apart from other things, they return an exit status
- Exit status of 0 implies successful
- Any other positive integer implies an error state (with the value indicating type)
- Also used as Boolean.
 - $0 \Rightarrow \text{True}; >0 \Rightarrow \text{False}$
(most typically 1)
- Exit status of last command available as `$?`, e.g. `echo $?`



Should be Exit Status 0

Aside: grep

`grep [options] <pattern string> <file> ...`

- Search for the specified pattern string in one or more files.
- Returns matches on stdout (or nothing)
- Also returns an exit status 0 (found) 1 (not found)

```
grep Alice Alice_in_Wonderland.txt > /dev/null
echo $?
```

Demo

- Let's look at

```
grep Alice Alice_in_Wonderland.txt >  
/dev/null  
echo $?
```

- What do you see if you're in the directory containing the text?
- What do you if you search with `fred` ?
- What do you see if you search with `Alice` ?
- Use the command `> empty_book.txt` to create a zero length file, and then run the search again looking for Alice in both the Alice text and the null book.

Conditionals: `if .. else`

- The conditional execution command use by Bash is fairly conventional, at least in appearance.

```
if <condition>
then
    <statements>
[elif <condition>
    <statements>] .....
[else
    <statements>]
fi
```

- The minimum statement uses `if then fi`

Conditionals: `if .. else`

- The `if <condition>` is evaluated and if true, the then statements are executed.
- Otherwise, if an `elif` clause exists its condition is evaluated, and if that is successful, its then statements are executed.
- This is repeated for each successive `elif` until either one is satisfied (and the then statements are executed) or no `elif` clauses remain.
- If neither the `if` condition, nor any of the `elif` conditions are satisfied, and an `else` clause exists, its statements are executed.

Conditionals: if .. else

```
if grep Alice Alice_in_Wonderland.txt >
/dev/null
then
    echo Found Alice
else
    echo Alice wasn\'t in Wonderland
fi
```

test

- `test <test expression>` is a program that doesn't output anything, but rather executes the test expression and returns the outcome in the exit status
- `man test` for all the tests. Some common examples:
 - d <directory> Tests if the directory exists
 - f <file> Tests if the file exists as ordinary file
 - s <file> Test if the file exists and is not 0 length
 - n <string> Is the string non-zero length
 - z <string> Is the string zero length

Demo

```
> empty_book.txt # create empty file
if test -f empty_book.txt
then
    echo All Good
else
    echo Not so good
fi
```

- What do I see
- What do I see if the test is `-s` ?
- What do I see if the test is `-n` ?

```
book=
if test -f $book ( .... etc)
```

What do I see now?

`[[..]]` **replace** `test`

- `test` is a program (`/bin/test`)
- Bash also implements built tests mimicking `test`
- Tests are between `[[` and `]]`
 - *leave space around brackets*

`[[-s empty_book.txt]]`

- `test` is ubiquitous; `[[]]` in Bash and ksh (also more efficient)

Testing numbers

- There are also infix tests which can be easier in the brackets version

`[[1038 < 999]]` tests whether string 1038 is less than string 999

– *try test a < b*

- Can also handle numerical comparisons

`[[1038 -lt 999]]`

`echo $?`

Testing numbers

```
#!/usr/bin/env bash
if [[ $1 -ge 75 ]]
then
    echo Excellent
elif [[ $1 -ge 65 ]]
then
    echo Very Good
elif [[ $1 -gt 50 ]]
then
    echo Good
elif [[ $1 -eq 50 ]]
then
    echo "Well, OK"
else
    echo Aaaaaaaaaaaaaagggggggggggggghhhhhhhh
fi
```

👉 👉 👉 Anti-bugging 👈 👈 👈

- Anti-bugging is to not simply assume that the input users provide is actually what the program expects, but to take steps to ensure it is, by adding prior tests.
 - *Sanity checks*
 - *This is important; GIGO is a thing*

Demo: Anti-bugging `count_occurrences`

- `count_occurrences` has two inputs, the text whose words are to be counted, and the number of top words to report



Starecat.com

Time for some
Anti-bugging!